

- ★ 100% EAS Guaranteed
- ★ Green Device Available
- ★ Super Low Gate Charge
- ★ Excellent CdV/dt effect decline
- ★ Advanced high cell density Trench technology

Product Summary




| BVDSS | RDS(on) | ID |
|-------|---------|------|
| -60V | 90mΩ | -13A |

Description

The FKD6113 is the high cell density trenched P-ch MOSFETs, which provide excellent RDS(on) and gate charge for most of the synchronous buck converter applications.

The FKD6113 meet the RoHS and Green Product requirement, 100% EAS guaranteed with full function reliability approved.

TO252 Pin Configuration



Absolute Maximum Ratings

| Symbol | Parameter | Rating | Units |
|---------------------------|---|------------|-------|
| V_{DS} | Drain-Source Voltage | -60 | V |
| V_{GS} | Gate-Source Voltage | ± 20 | V |
| $I_D @ T_C = 25^\circ C$ | Continuous Drain Current, $V_{GS} @ -10V^1$ | -13 | A |
| $I_D @ T_C = 100^\circ C$ | Continuous Drain Current, $V_{GS} @ -10V^1$ | -8.3 | A |
| $I_D @ T_A = 25^\circ C$ | Continuous Drain Current, $V_{GS} @ -10V^1$ | -3.3 | A |
| $I_D @ T_A = 70^\circ C$ | Continuous Drain Current, $V_{GS} @ -10V^1$ | -2.7 | A |
| I_{DM} | Pulsed Drain Current ² | -26 | A |
| EAS | Single Pulse Avalanche Energy ³ | 29.8 | mJ |
| I_{AS} | Avalanche Current | 24.4 | A |
| $P_D @ T_C = 25^\circ C$ | Total Power Dissipation ⁴ | 31.3 | W |
| $P_D @ T_A = 25^\circ C$ | Total Power Dissipation ⁴ | 2 | W |
| T_{STG} | Storage Temperature Range | -55 to 150 | °C |
| T_J | Operating Junction Temperature Range | -55 to 150 | °C |

Thermal Data

| Symbol | Parameter | Typ. | Max. | Unit |
|-----------------|--|------|------|------|
| $R_{\theta JA}$ | Thermal Resistance Junction-Ambient ¹ | --- | 62 | °C/W |
| $R_{\theta JC}$ | Thermal Resistance Junction-Case ¹ | --- | 4 | °C/W |

P-Channel Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)







| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|--|--|--|------|--------|-----------|----------------------------|
| BV_{DSS} | Drain-Source Breakdown Voltage | $V_{\text{GS}}=0\text{V}$, $I_D=-250\mu\text{A}$ | -60 | --- | --- | V |
| $\Delta \text{BV}_{\text{DSS}}/\Delta T_J$ | BV_{DSS} Temperature Coefficient | Reference to 25°C , $I_D=-1\text{mA}$ | --- | -0.023 | --- | $\text{V}/^\circ\text{C}$ |
| $R_{\text{DS}(\text{ON})}$ | Static Drain-Source On-Resistance ² | $V_{\text{GS}}=-10\text{V}$, $I_D=-10\text{A}$ | --- | --- | 90 | $\text{m}\Omega$ |
| | | $V_{\text{GS}}=-4.5\text{V}$, $I_D=-5\text{A}$ | --- | --- | 115 | |
| $V_{\text{GS}(\text{th})}$ | Gate Threshold Voltage | $V_{\text{GS}}=V_{\text{DS}}$, $I_D=-250\mu\text{A}$ | -1.0 | --- | -2.5 | V |
| $\Delta V_{\text{GS}(\text{th})}$ | $V_{\text{GS}(\text{th})}$ Temperature Coefficient | | --- | 4.65 | --- | $\text{mV}/^\circ\text{C}$ |
| I_{DSS} | Drain-Source Leakage Current | $V_{\text{DS}}=-48\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=25^\circ\text{C}$ | --- | --- | 1 | uA |
| | | $V_{\text{DS}}=-48\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=55^\circ\text{C}$ | --- | --- | 5 | |
| I_{GSS} | Gate-Source Leakage Current | $V_{\text{GS}}=\pm 20\text{V}$, $V_{\text{DS}}=0\text{V}$ | --- | --- | ± 100 | nA |
| g_{fs} | Forward Transconductance | $V_{\text{DS}}=-5\text{V}$, $I_D=-4\text{A}$ | --- | 8.7 | --- | S |
| R_g | Gate Resistance | $V_{\text{DS}}=0\text{V}$, $V_{\text{GS}}=0\text{V}$, $f=1\text{MHz}$ | --- | 15 | --- | Ω |
| Q_g | Total Gate Charge (-4.5V) | $V_{\text{DS}}=-12\text{V}$, $V_{\text{GS}}=-4.5\text{V}$, $I_D=-6\text{A}$ | --- | 11.8 | --- | nC |
| Q_{gs} | Gate-Source Charge | | --- | 1.9 | --- | |
| Q_{gd} | Gate-Drain Charge | | --- | 6.5 | --- | |
| $T_{\text{d}(\text{on})}$ | Turn-On Delay Time | $V_{\text{DD}}=-15\text{V}$, $V_{\text{GS}}=-10\text{V}$, $R_G=3.3\Omega$, $I_D=-1\text{A}$ | --- | 8.8 | --- | ns |
| T_r | Rise Time | | --- | 19.6 | --- | |
| $T_{\text{d}(\text{off})}$ | Turn-Off Delay Time | | --- | 47.2 | --- | |
| T_f | Fall Time | | --- | 9.6 | --- | |
| C_{iss} | Input Capacitance | $V_{\text{DS}}=-15\text{V}$, $V_{\text{GS}}=0\text{V}$, $f=1\text{MHz}$ | --- | 1080 | --- | pF |
| C_{oss} | Output Capacitance | | --- | 73 | --- | |
| C_{rss} | Reverse Transfer Capacitance | | --- | 50 | --- | |






Diode Characteristics

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|-----------------|--|---|------|------|------|------|
| I_s | Continuous Source Current ^{1,5} | $V_G=V_D=0\text{V}$, Force Current | --- | --- | -13 | A |
| I_{SM} | Pulsed Source Current ^{2,5} | | --- | --- | -26 | A |
| V_{SD} | Diode Forward Voltage ² | $V_{\text{GS}}=0\text{V}$, $I_s=-1\text{A}$, $T_J=25^\circ\text{C}$ | --- | --- | -1 | V |

Note :

- 1.The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$
- 3.The EAS data shows Max. rating . The test condition is $V_{\text{DD}}=-25\text{V}$, $V_{\text{GS}}=-10\text{V}$, $L=0.1\text{mH}$, $I_{\text{AS}}=-24.4\text{A}$
- 4.The power dissipation is limited by 150°C junction temperature
- 5.The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation.

P-Channel Typical Characteristics

Fig.1 Typical Output Characteristics

Fig.3 Forward Characteristics of Reverse

Fig.5 Normalized $V_{GS(th)}$ v.s T_J

Fig.2 On-Resistance v.s Gate-Source

Fig.4 Gate-Charge Characteristics

Fig.6 Normalized $R_{DS(on)}$ v.s T_J


Fig.7 Capacitance

Fig.8 Safe Operating Area

Fig.9 Normalized Maximum Transient Thermal Impedance

Fig.10 Switching Time Waveform

Fig.11 Unclamped Inductive Switching Waveform